MARINE GENERATORS

29 GS/GSC

Single-Phase

General data

Maximum power*	28.4 kW (28.4 kVA)	**Voltage**	230 V
Prime Power**	25.8 kW	**Amperage**	123.5 A
Frequency	50 Hz	**Phases**	1

Dimensions and weights

Total length without canopy	1422 mm	**Total length with canopy**	1600 mm
Total width without canopy	740 mm	**Total width with canopy**	740 mm
Total height without canopy	783 mm	**Total height with canopy**	837 mm
Dry weight without canopy	680 Kg	**Dry weight with canopy**	714 Kg

Engine

Base engine manufacturer	Mitsubishi	**Diameter**	94 mm (3.7 in)
Model	MINI-74	**Stroke**	120 mm (4.72 in)
Type	Diesel, 4 stroke	**Compression ratio**	22:1
Engine RPM	1500	**Injection system**	Mechanical and indirect
Number of cylinders	4	**Intake system**	Naturally aspirated
Total displacement	3331 cc	**SAE Flywheel housing**	SAE 3
Oil	SAE 15W40	**Coolant capacity**	13 L (3.43 gal)
Oil capacity	10 L (2.64 gal)	**Flywheel**	SAE 11 1/2
Power	30.8 kW (41.89 CV)	**Coolant flow rate**	105 l/min (27.74 gal/m)
Salt water flow rate	37.5 l/min (9.91 gal/m)	**Intake air flow rate**	2.25 m3/m
Exhaust type	Wet exhaust elbow	**V-Belt Protection**	Optional

Rating conditions according to ISO 3046 (100 kPa barometric pressure, 30 % relative humidity abd 25 °C (77 ° F))
* Maximum output power: maximum power supplied by the genset at full load
** Prime Power: rated power according to ISO 3046 and ISO 8528-1. 10 % overload capacity one hour in twelve hours.
Fuel system details
1 kW 1,36 CV 1 kW 1,36 HP (metric) 1 kW 1,36 CH
45484 - 7/24

Fuel system details

Consumption 25%	2.9 l/h (0.77 gal)	**Fuel type**	Diesel
Consumption 50%	4.3 l/h (1.14 gal)	**Fuel standards**	Fueloil diesel ASTM
Consumption 75%	6.1 l/h (1.61 gal)	**Injection pump type**	In line
Consumption 100%	8.2 l/h (2.17 gal)	**Governor type**	Mechanical

Electrical system

Battery voltage	12 V	**Stop solenoid type**	ETR
Starter motor	2.2 kW	**Alternator**	50 A
Earth isolated	Optional	**IP 65 box kit**	Optional
SCO 11 double panel	Optional	**Current transformers**	Optional

Installation details

Exhaust hose inner diameter	75 mm (2.95 in)	**Maximum fuel lift height**	0.6 m (1.97 ft)
Sea water hose inner diameter	32 mm (1.26 in)	**Maximum raw water lift height**	2.5 m (98.43 in)
Fuel feeding hose inner diameter	8 mm (0.31 in)	**Maximum sea water temperature**	32 º (89.6 ºF)
Fuel return hose inner diameter	- (- in)	**Maximum installation angle*** **	15 º
Minimum battery capacity	12 V 95 Ah		

Alternator details

Brand	Meccalte	**Cos Phi**	1
Model	ECP32 1M 4 C	**Tropicalized**	Yes
Regulator type	DSR	**Excitation system**	BRUSHLESS
Number of poles	4	**Voltage regulation accuracy****	0,01
Isolation type*	H	**Standards**	EN60034-1, IEC 60034-1
IP protection	23	**Alternator type**	SÍNCRONO

Standard equipment

4 m electrical wiring extension	SCO 11 control panel
Oil extraction pump	Owner´s and alternator manual
Rigid bed	Packaging
Silentblocks	

Optional accessories

Siphon break kit mandatory if generator is below waterline	Wet Exhaust System
Engine electrical system at 24 V	Water Filters
Service/Cruise Kits: fuel and oil filters, raw water pump, impeller, alternator belt,...	Sea water cock
Dry Exhaust system	Welcome Kit

* Other protections available
** With load from 0 to 100%, speed variation from -2% up to +5%, power factor 0,8 linear and balanced load.
*** In all directions
For other requirements please contact the Sales Dept.
45484 - 7/24

SCO 11 Panel

General Description

- Graphic LCD with light, 128 x 64 pixels display
- Genset measures (see Display Information)
- Configuration protected by user and password
- Running hour indication
- Multilengüaje
- Event history log
- Genset protections (see Alarm Management)
- Preheating function
- D+ pre-excitation Terminal
- Built-in PLC function
- CAN bus information with SAE J1939 protocol
- Maintenance hours control
- Dimensions 195 x 135 x 47 mm
- Board Cutting 172 x 112 mm
- Weight 450 g

Alarm Management

- Shut Downs (SD)
- High coolant temperature
- Low oil pressure
- Overspeed
- Overload*
- Short circuit*
- Overcurrent*
- Over/Under voltage
- Over/Under frequency
- Emergency stop
- Warnings (WRN)
- High coolant temperature
- Low oil pressure
- Over/Under Battery voltage
- Maintenance request
- Sensor failure detection (FLS)

Power Supply

- Voltage supply 12/24 DC with fuse protection
- Consumption 80mA (12V) or 51 (24V)

Operating Conditions

- Operating temperature -20+70 °C
- Humidity 95 % without condensation
- Front Panel Protection IP65
- Standard Conformity
- EN 61000-6-2, EN 61000-6-4, EN 61010-1
- EN 60068-2-6 (2÷25 Hz / ±1,6 mm; 25÷100 Hz / 4.0 g)
- EN 60068-2-30:2005 25/55°C, RH 95%, 48hours
- EN 60529 (front panel IP65, back side IP20)

Display Information

- Measurement
- L1-L3 Voltage (V), Frequency (Hz), Oil Pressure (bar)
- Coolant Temperature (°C), Battery voltage (V), RPM
- Active Power* (kW), Apparent, Power* (kVA), Current* (A), PF*
- History log

Operating modes

- OFF Mode
- MAN Mode (manual start/stop engine)
- AUT Mode (auto start/stop engine)

Dimensions





Authorized dealer

Detailed drawings, brochures and manuals are available on the web soleadvance.com. All rights reserved.
Technical specifications, data and presentation are subjected to variations, changes and updates without prior notice
Non-contractual information.